Plug Fuses Dual-Element, Time-Delay, Edison Base 125 Volts, 1–30 Amps

Type T



CATALOG SYMBOL: T DUAL-ELEMENT, TIME-DELAY 1 TO 30A 125VAC OR LESS U.L. LISTED

(GUIDE #JEFV, FILE # E12112)

Electrical Ratings (Catalog Symbol and Amperes)

125 Volts	125 Volts	125 Volts
T-3/10	T-2-1/4	T-7
T-4/10	T-2-1/2	T-8
T-1/2	T-2-8/10	T-9
T-6/10	T-3	T-10
T-8/10	T-3-2/10	T-12
T-1	T-3-1/2	T-14
T-1-1/8	T-4	T-15
T-1-1/4	T-4-1/2	T-20
T-1-4/10	T-5	T-25
T-1-6/10	T-5-6/10	T-30
T-1-8/10	T-6	_
T-2	T-6-1/4	_


Package Quantity and Weight

Ampere	Quantity		Weight	Weight	
Ratings	Box	Card	Per Box	Per 5 Cards	
3/10-14A	4	1	0.210	0.46	
15, 20, 25, & 30A	4	3	0.25	1.07	

• Heavy Duty Time-Delay Plug Fuse.

- Use to protect critical motor circuits or motors that cycle on/off frequently.
- An industrial/commerical grade product with exclusive dualelement construction.
- Edison base size.
- These fuses thread into fuse receptacles.
- The Heavy Duty T fuses are industrial strength products, featuring Bussmann's exclusive Dual-Element construction.
- This spring loaded design provides superior short circuit and overload protection.
- The T fuses have more time-delay than the medium duty fuses in order to better protect industrial motors and critical residential circuits.

Time-Current Characteristics-Total Clear



This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

